



NOTES:  
 1.MATERIAL:  
 BODY:HI-TEMP. PLASTIC,BLACK,UL 94V-0  
 TERMINAL:COPPER ALLOY,T=0.12mm  
 SHELL:STAINLESS STEEL,T=0.15mm  
 2.FINISH:  
 TERMINAL:50u" Ni MIN UNDER PLATING OVER ALL  
 GOLD FLASH ON CONTACT AREA  
 60-200u" MATTE TIN PLATED ON SOLDER TAIL AREA  
 SHELL:50u" Ni MIN UNDER PLATING OVER ALL  
 60-200u" TIN PLATED ON SOLDER TAIL AREA  
 3.ALL DIMENSIONS MARKED ▼ MUST BE CONTROLLED BY QC

REV.	ECN NO.	DESCRIPTION	DATE	REV.	FINISH: SEE NOTE	MATERIAL:		DRAW:	PART NO: B38-AB03F15C
D	E1703032A	依实物修改尺寸公差	03/01'2017	UNITS: mm	GENERAL TOLERANCE				
C	E1701007A	增加尺寸管控	01/11'2017	DATE: 10/07'2013	X. ±0.20	X° ±2.00°		CHECKED:	TITLE: 1.5H 测压式的Battery
B	E1403045A	端子锡脚电镀由亮锡->雾锡	03/10'2014	SCALE: 10:1	.X ±0.15	.X° ±1.00°		APPROVE:	DRAWING NO:
A		NEW	10/07'2013	SHEET: 1/1	.XX ±0.10	.XX° ±0.50°			
				REV. A	.XXX ±0.05	.XXX° ±0.10°			

 鸿日达电子科技有限公司  
 HONGRIDA ELECTRONIC TECHNOLOGY CO.,LTD.