


RECOMMENDED PCB LAOUT  
TOLERANCE (.XX ± 0.05)

NOTES:  
 1. MATERIAL:  
 BODY: HI-TEMP. PLASTIC, BLACK, UL 94V-0  
 TERMINAL: COPPER ALLOY, T=0.20mm  
 SHELL: STAINLESS STEEL T=0.15mm  
 2. FINISH:  
 TERMINA:  
 40u" Ni MIN UNDER PLATING OVER ALL  $\Delta$   
 Au 2u" MIN ON CONTACT AREA  
 60-200u" TIN PLATED ON SOLDER AREA  
 SHELL:  
 50u" Ni MIN UNDER PLATING OVER ALL  
 GOLD FLASH ON SOLDER AREA  
 3. ALL DIMENSIONS MARKED ▼ MUST BE CONTROLLED BY QC

				UNITS: mm	GENERAL TOLERANCE		DRAW:	PART NO:
				DATE: 01/21/2015	X. ±0.20	X.' ±2.00'	CHECKED:	TITLE: 3PIN 2.50 PITCH BATTERY CONN.
B	E1707231A	端子电镀规格变更	07/29/2017	SCALE: 8 / 1	.X ±0.15	.X' ±1.00'	APPROVE:	DRAWING NO:
A		NEW	01/21/2015	SHEET: 1 / 1	.XX ±0.10	.XX' ±0.50'	 昆山捷皇电子精密科技有限公司 HONGRIDA ELECTRONIC TECHNOLOGY CO, LTD.	
REV.	ECN NO.	DESCRIPTION	DATE	REV. A	FINISH: SEE NOTE	