


RECOMMENDED PCB LAYOUT
TOLERANCE (.XX ± 0.05)

- NOTES:
- MATERIAL:
BODY: HI-TEMP. PLASTIC, BLACK, UL 94V-0
TERMINAL: COPPER ALLOY, T=0.20mm
SHELL: STAINLESS STEEL T=0.15mm
 - FINISH:
TERMINA:
40u" Ni MIN UNDER PLATING OVER ALL Δ_B
AU 2u" MIN ON CONTACT AREA
60-200u" TIN PLATED ON SOLDER AREA
 - SHELL:
50u" Ni MIN UNDER PLATING OVER ALL
GOLD FLASH AU ON SOLDER AREA
 - ALL DIMENSIONS MARKED ▼ MUST BE CONTROLLED BY QC
 - RESISTANCE TO CURRENT: 3A MAX

				UNITS: mm	GENERAL TOLERANCE		DRAW:	PART NO:
				DATE: 12/25/2014	X. ±0.20	X.' ±2.00'	CHECKED:	TITLE: 4PIN 2.50 PITCH BATTERY CONN.
B	E1707231A	端子电镀规格变更	07/29/2017	SCALE: 8 / 1	.XX ±0.10	.XX' ±0.50'	APPROVE:	DRAWING NO:
A		NEW	12/25/2014	SHEET: 1 / 1	MATERIAL:		 昆山捷皇电子精密科技有限公司 HONGRIDA ELECTRONIC TECHNOLOGY CO., LTD.	
REV.	ECN NO.	DESCRIPTION	DATE	REV. A	FINISH: SEE NOTE			