



RECOMMENDED P. C. B LAYOUT  
TOLERANCE : ±0.05mm

- NOTES:
- MATERIAL:  
HOUSING: LCP, BLACK, UL 94V-0  
TERMINAL: COPPER ALLOY, T=0.15MM  
SHELL: STAINLESS STEEL T=0.20MM
  - FINISH:  
CONTACT: 50U'' MIN NI PLATING OVER ALL  
GOLD FLASH ON THE CONTACT AREA & SOLDER AREA  
SHELL: 50U'' MIN NI PLATING OVER ALL  
GOLD FLASH ON THE SOLDER AREA
  - ALL DIMENSIONS MARKED ▼ MUST BE CONTROLLED BY QC
  - ALL DIMENSIONS MARKER (XX) MUST BE MEASURED BY FAI.
  - GP PASSED ACCORD WITH HRD-RoHS-219 STANDARD

T-CARD PIN NO.	PIN NO.
T1	DAT2
T2	CD/DAT3
T3	CMD
T4	VDD
T5	CLK
T6	VSS
T7	DATO
T8	DAT1
SIM CARD PIN NO.	PIN NO.
P1-A/B	VCC
P2-A/B	RST
P3-A/B	CLK
P5-A/B	GND
P6-A/B	VPP
P7-A/B	I/O

F	E1608337A	取消压料 加强塑胶强度	08/17/2016	UNITS: mm	GENERAL TOLERANCE		DRAW:	PART NO: S75-0B20F46A
E	E1509340A	锡脚增加缺口 增加焊接牢固性	09/12/2015	DATE: 06/14/2014	X. ±0.30	X.° ±2.00°	CHECKED:	TITLE: 双SIM CARD+TF CARD 成品H=4.60mm
D	E1505206A	修改图面与实物相符 增加塑胶压端子位置	05/21/2015	SCALE: 4:1	.X ±0.20	.X° ±1.00°	APPROVE:	DRAWING NO:
C	E1501058A	屏蔽罩通空位置修改	01/16/2015	SHEET: 1/1	.XX ±0.10	.XX° ±0.50°		
REV.	ECN NO.	DESCRIPTION	DATE	REV. A	.XXX ±0.05	.XXX° ±0.10°		

昆山捷皇电子精密科技有限公司  
HONGRIDA ELECTRONIC TECHNOLOGY CO., LTD.