



RECOMMENDED PCB LAYOUT
 GENERAY TOLERANCE ± 0.05

NOTES:

- MATERIAL:
 HOUSING: LCP, BLACK, UL 94V-0
 CONTACT: PHOSPHOR BRONZE, T=0.08MM
 SHELL: STAINLESS STEEL T=0.10MM
- FINISH:
 CONTACT: 50u"min PLATING OVER ALL GOLD FLASH ON THE CONTACT AREA AND SOLDER AREA
 SHELL: SELECTIVE GOLD FLASH IN SOLDER TAIL AREA
 50u"NI min. PLATING OVER ALL
- GP PASSED ACCORD WITH RoHS STANDARD.
- ALL DIMENSIONS MARKED ▼ MUST BE CONTROLLED BY QC.
- ALL DIMENSIONS MARKED (XX) MUST BE CONTROLLED BY QC.

PIIN/NO.	ASSIGNMENT
C1	Vcc(SUPPLY VOLTAGE)
C2	RST(RESET SIGNAL)
C3	CLK (CLOCK SIGNAL)
CD	DETECT SEITCH
C5	GND
C6	Vpp (VARIABLE SUPPLY BOLTAGE)
C7	I/O (DATA INPUT/OUTPUT)

REV.	ECN NO.	DESCRIPTION	DATE	REV.	FINISH: SEE NOTE	SCALE:	UNITS: mm	GENERAL TOLERANCE	DRAW:	PART NO:
B	E1608348A	修改端子铁壳结构	08/19/2016	8 / 1		X. ±0.20 .X ±0.15 .XX ±0.10 .XXX ±0.05	mm	X. ±0.20 .X ±0.15 .XX ±0.50 .XXX ±0.10	CHECKED:	S139-0B07F13A
A		NEW	07/04/2016	1 / 2					APPROVE:	TITLE: 1.35H NANO SIM CARD CONN.
										DRAWING NO:



昆山捷皇电子精密科技有限公司
 HONGRIDA ELECTRONIC TECHNOLOGY CO., LTD.